
GRAPHIC EQUALIZER EQ700

Ultimate 7-Band Graphic Equalizer

Thank you for showing your confidence in us by purchasing the BEHRINGER GRAPHIC EQUALIZER EQ700. This high-quality stompbox is specifically designed to provide complete tone control and eliminate unwanted feedback. It allows 7-band sound shaping and feedback elimination from 100 Hz to 6.4 kHz with a powerful 15 dB boost/cut per band.

1. Controls



- 1 The **7-band EQ** faders allow to boosting/cutting single frequency ranges from 100 Hz to 6.4 kHz at +15 dB.
- The LEVEL fader adjusts the output level. It can be used to achieve effective volume "boost" or "cut."
- This **LED** illuminates when the EO is activated. It also serves as a battery level indicator.
- 4 Use the footswitch to activate/deactivate the EO.
- Use this ¼" TS IN connector to plug in the instrument cable.
- $^{\circ}$ The $\frac{1}{4}$ " TS **OUT** connector sends the signal to your amp.

Use the **DC IN** connection at the front of the unit to plug in a 9 V power supply (not included).

The **BATTERY COMPARTMENT** is located underneath the pedal cover. To install or replace the 9 V battery, press the hinges with a ballpen and remove the pedal cover. Be careful not to scratch the unit.

The EQ700 has no on/off switch. As soon as you insert the jack into the in connector, the EQ700 begins running. When not using the EQ700, remove the jack from the in connector. This extends the life of the battery.

The SERIAL NUMBER is located at the bottom.



2. Safety Instructions

Do not use near water, or install near heat sources. Use only authorized attachments/accessories. Do not service product yourself. Contact our qualified servicing personnel for servicing or repairs, especially when power supply cord or plug is damaged.

3. Warranty

Please register your new BEHRINGER equipment right after your purchase by visiting http://behringer.com and read the terms and conditions of our warranty carefully.

4. Specifications

In	
Connector	1⁄4" TS
Impedance	500 kΩ
Out	
Connector	1⁄4" TS
Impedance	1 kΩ
Power Supply	
1 ower suppry	9 V⋯, 100 mA regulated
BEHRINGER PSU-SB	
PSU-SB-CN BEHRINGER	220 VAC adaptor China
PSU-SB-EU BEHRINGER	230 VAC adaptor Europe
PSU-SB-JP BEHRINGER	100 VAC adaptor Japan
PSU-SB-SAA BEHRINGER	240 VAC adaptor Australia
PSU-SB-UK BEHRINGER	240 VAC adaptor UK
PSU-SB-UL BEHRINGER	115 VAC adaptor USA

r

Physical/Weight	
Dimensions	approx. 2 1/8 x 2 3/4 x 4 4/5"
(H x W x D)	approx. 54 x 70 x 123 mm
Weight	approx. 0.73 lbs / 0.33 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may therefore differ from those listed or shown.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM.). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HERRIC. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP PAND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTRAING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTED IN AUTHORISE CROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC Group IP Ltd. Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Wirgin Islands

