

### **Technical Specifications**



# **DIGITAL MONITOR SPEAKERS MS**20

24-Bit/192 kHz Digital 20-Watt Stereo Near Field Monitors



EN

## **EN DIGITAL MONITOR SPEAKERS MS20**

#### 24-Bit/192 kHz Digital 20-Watt Stereo Near Field Monitors

- 2-way active studio monitors ideally suited for computer studios, audio and multimedia workstations and keyboard monitoring
- Built-in 2 x 10-Watt powerful amplifiers with immense headroom
- Powerful woofers and high-resolution tweeters provide an ultra-linear frequency response
- Ultra-high resolution 24-bit/192 kHz D/A converters for an incredible dynamic range
- Optical and coaxial inputs to directly connect digital audio sources by S/PDIF interface
- Two stereo analog inputs featuring 1/8" TRS and stereo RCA connectors can be used simultaneously or mixed with a digital stereo source
- Individual volume controls for both Line inputs plus Bass and Treble EQ controls
- **1**/4" TRS headphone connector with auto-mute loudspeaker function easily accessible on the front panel
- Magnetically shielded for placement near computer monitors
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

### **Specifications**

| dspeakers          |                                  |
|--------------------|----------------------------------|
| Tweeter            | Ø 65 mm (2 ½"), 8 Ω              |
| Woofer             | Ø 92 mm (3 5⁄s"), 4 Ω            |
| io Inputs          |                                  |
| Line 1             | 1⁄8" TRS stereo, impedance 20 kΩ |
| Line 2             | 2 RCA, impedance 20 k $\Omega$   |
| tal Inputs         |                                  |
| Optical            | TOSLINK                          |
| Coaxial            | RCA                              |
| Converter          | 24-bit                           |
| Sample rate        | < 192 kHz                        |
| em Specifications  |                                  |
| Output power       | 2 x 10 W                         |
| Frequency response | 65 Hz to 25 kHz                  |

#### **Power Supply**

| USA/Canada            | 120 V~, 60 Hz          |
|-----------------------|------------------------|
| Europe/U.K./Australia | 230 V~, 50 Hz          |
| China                 | 220 V~, 50 Hz          |
| Japan                 | 100 V~, 50 - 60 Hz     |
| eneral export model   | 120/230 V~, 50 - 60 Hz |
| ower consumption      | 80 W                   |

| Dimensions (H x W x D) | 239 x 154 x 187 mm (9.4 x 6.1 x 7.4") |
|------------------------|---------------------------------------|
| Weight                 | 5.8 kg (12.8 lbs)                     |

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph, or statement contained herein. Technical specifications, appearances and other information are subject to change without notice. All trademarks are the property of their respective owners. MIDAS, KLARK TEKNIK, TURBOSOUND, BEHRINGER, BUGERA and DDA are trademarks or registered trademarks of MUSIC Group IP Ltd. If their respective owners. MIDAS, KLARK TEKNIK, TURBOSOUND, BEHRINGER, BUGERA and DDA are trademarks or registered trademarks of MUSIC Group IP Ltd. MUSIC Group IP Ltd.

