

THANK YOU FOR CHOOSING A MORLEY PEDAL. YOU NOW OWN THE BEST PEDAL MADE!

Please take a few minutes to familiarize yourself with the features of your new pedal. We hope you enjoy using it as much as we enjoyed building it.

ABOUT OUR ELECTRO-OPTICAL CIRCUITRY:

An LED (Light Emitting Diode) shines on an LDR (Light Dependent Resistor). A shutter alters light between the two components controlling functions like Wah, volume and switching. Electro-Optical design ensures smooth pedal control without unwanted noise typical with potentiometer (pot) controlled pedals. No more pots to get scratchy and wear out!

ABOUT THE CONNECTIONS:

9V: To ensure noise free operation, ONLY Morley's 9VDC 300 mA regulated adapter should be used (center polarity is negative)

IN: Input jack. Plug instrument into this jack using 1/4" guitar cable.

OUT: Connect amplifier to this jack using a 1/4" guitar cable.

USING AN AC ADAPTER:

All Morley pedals use Morley's 9VDC 300 milliamp regulated adapter. Center pin polarity is negative.

Using a non-regulated adapter could cause a low frequency hum in your amplifier.

Using an adapter with the wrong polarity may damage the pedal.

USING A BATTERY:

All Morley pedals are designed to use one 9V battery when not using an adapter. We suggest you use a good quality alkaline battery. To prolong battery life, unplug your cord completely from the input jack when not using the pedal. When the pedal is not used for extended periods, remove the battery from the pedal. Our Quick Clip battery door allows for easy access to battery compartment.

TWO YEAR WARRANTY

All Morley® pedals are warranted for two years from date of purchase. To obtain warranty service, call Morley toll free at 1-800-284-5172 x15

STEREO CHORUS VOLUME (MODEL SCV) FEATURES:

- **Electro-Optical:** No pots to get scratchy or wear out.
- **True Tone Buffer Bypass:** Ensures strongest, clearest tone in all pedal modes.
- **Chorus Depth:** Controls Depth of Chorus. Depth is the moving change in frequency.
- **Chorus Speed:** Controls Speed of Chorus. Speed is timing of Chorus Depth change.
- **Stereo Outputs:** Use a single output to one amp or use two outputs to two amps for that extra wide Chorus Sound.

SCV SPECIFICATIONS:

Power: 9V Battery or 9VDC 300mA regulated
(polarity: center negative)

Indicator: Right LED on = Pedal Powered Up

Indicator: Left LED on = Chorus On

Dimensions: 9.13" L x 5.88" W x 2.75" H

Current Draw: 19 mA @ 9VDC

Weight: 3.7 lb./ 1.68 kg

